



PIN	1	2	3	4	5	6	7	8	9	10	11
SYMBOL	VSS	VDD	V0	RS	/WR	/RD	/CS	CSE	BUSY	/INT	/RST
PIN	12	13	14	15	16	17	18	19	20	21	22
SYMBOL	D0	D1	D2	D3	D4	D5	D6	D7	VEE	LEDA	LEDK

- NOTES:
1. DISPLAY TYPE: STN/BLUE MODE
 2. VIEWING DIRECTION: 12:00
 3. POLARIZER MODE: TRANSMISSIVE/NEGATIVE
 4. DRIVE METHOD: 1/128 DUTY 1/12 BIAS
 5. VDD=5.0V, VLED=5.0V, VDP=-1.75V
 6. LCD CONTROLLER: RA8806
 7. OPERATING TEMP: -20°C~+70°C
 8. STORAGE TEMP: -30°C~+80°C

Internal DC-DC,
external
potentiometers
adjusting the
contrast.

REV	DATE	DESCRIPTION	DESIGNED	CHECK	APPROVED

SHIJIAZHANG CHUANGDI TECHNOLOGY CO.,LTD
 CUSTOMER'S CODE:
 MODEL NO.: CSM-240128B
 REV: A-0
 UNMARKED TOLERANCE: ±0.2mm
 Page: III